


MC 系列连接器 MC Terminal Blocks

2.5mm间距 Pitch: 2.5mm

MC-RJ2.5HXXP-0001

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	[N·m]	-	MC-RJ2.5HXXP-0001	2-24	
额定电流 Rated current	[A]	4	扭矩 Torque	[N·m]	-			
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	[N·m]	-			
硬导线截面积 Solid	[mm²][AWG]	0.2-0.5	扭矩 Torque	[N·m]	-	附件Accessory		
柔性导线截面积 Flexible	[mm²][AWG]	0.2-0.5	剥线长度 Strip length	[mm]	7-8			
额定冲击电压 Rated impulse voltage	[KV]	2.5						



3.5mm间距 Pitch: 3.5mm

MC-RA3.5HXXC-K-0001




产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	[N·m]	M2	MC-RA3.5HXXC-K-0001	2-24	
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	0.2	MC-RA3.5HXXC-K-0001	2-24	
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	[N·m]	M2.5	MC-RA3.5HXXC-I-0001	2-24	
硬导线截面积 Solid	[mm²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	0.3			
柔性导线截面积 Flexible	[mm²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	7-8			
额定冲击电压 Rated impulse voltage	[KV]	2.5						



MC-RA3.5HXXC-0001

MC-RA3.5HXXC-K-0001

MC-RA3.5HXXC-I-0001



3.5mm间距 Pitch: 3.5mm

MC-RE3.5VXXC-K-0001




产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	[N·m]	M2	MC-RE3.5VXXC-0001	2-24	
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	0.2	MC-RE3.5VXXC-K-0001	2-24	
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	[N·m]	M2.5	MC-RE3.5VXXC-I-0001	2-24	
硬导线截面积 Solid	[mm²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	0.3	MC-RE3.5VXXC-R-0001	2-24	
柔性导线截面积 Flexible	[mm²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	7-8	MC-RE3.5VXXC-RK-0001	2-24	
额定冲击电压 Rated impulse voltage	[KV]	2.5						



MC-RE3.5VXXC-0001



MC-RE3.5VXXC-K-0001

MC-RE3.5VXXC-I-0001



MC-RE3.5VXXC-R-0001

MC-RE3.5VXXC-RK-0001





2.5mm间距 Pitch: 2.5mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	[N·m]	-	MC-PA2.5HXX-0002	2-24	
额定电流 Rated current	[A]	4	扭矩 Torque	[N·m]	-	MC-PA2.5VXX-0002	2-24	
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	[N·m]	-	MC-PA2.5VXX-0002	4-48	
硬导线截面积 Solid	[mm²][AWG]	-	扭矩 Torque	[N·m]	-	MC-PA2.5HXX-0002	4-48	
柔性导线截面积 Flexible	[mm²][AWG]	-	剥线长度 Strip length	[mm]	7-8			
额定冲击电压 Rated impulse voltage	[KV]	2.5						



MC-PA2.5VXX-0002

MC-PA2.5HXX-0002



MC-DPA2.5VXX-0002

MC-DPA2.5HXX-0002



3.5mm间距 Pitch: 3.5mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	[N·m]	-	MC-RJ3.5HXXP-0001	2-24	
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	-	MC-RJ3.5HXXP-K-0001	2-24	
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	[N·m]	M2.5	MC-RJ3.5HXXP-I-0001	2-24	
硬导线截面积 Solid	[mm²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	3			
柔性导线截面积 Flexible	[mm²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	8-9			
额定冲击电压 Rated impulse voltage	[KV]	2.5						

MC-RJ3.5HXXP-0001

MC-RJ3.5HXXP-K-0001

MC-RJ3.5HXXP-I-0001

