



3.81mm间距 Pitch: 3.81mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	M2	MC-RA3.81HXXC-0001	2-24	MC-IP3.81-X		
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	0.2	MC-RA3.81HXXC-K-0001	2-24		
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	M2.5	MC-RA3.81HXXC-I-0001	2-24			
硬导线截面积 Solid	[mm ²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	0.3				
柔性导线截面积 Flexible	[mm ²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	6-7				
额定冲击电压 Rated impulse voltage	[KV]	2.5							


MC-RA3.81HXXC-0001



MC-RA3.81HXXC-K-0001




MC-RA3.81HXXC-I-0001




3.81mm间距 Pitch: 3.81mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	M2	MC-RAF3.81HXXC-0001	2-24	MC-IP3.81-X		
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	0.2	MC-RAF3.81HXXC-K-0001	2-24		
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	M2.5	MC-RAF3.81HXXC-I-0001	2-24			
硬导线截面积 Solid	[mm ²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	0.3				
柔性导线截面积 Flexible	[mm ²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	8-9				
额定冲击电压 Rated impulse voltage	[KV]	2.5							


MC-RAF3.81HXXC-0001



MC-RAF3.81HXXC-K-0001




MC-RAF3.81HXXC-I-0001




3.81mm间距 Pitch: 3.81mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	M2	MC-RE3.81VXXC-0001	2-24	MC-IP3.81-X		
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	0.2	MC-RE3.81VXXC-K-0001	2-24		
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	M2.5	MC-RE3.81VXXC-I-0001	2-24			
硬导线截面积 Solid	[mm ²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	0.3	MC-RE3.81VXXC-R-0001	2-24		
柔性导线截面积 Flexible	[mm ²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	7-8	MC-RE3.81VXXC-RK-0001	2-24		
额定冲击电压 Rated impulse voltage	[KV]	2.5							


MC-RE3.81VXXC-0001




MC-RE3.81VXXC-K-0001




MC-RE3.81VXXC-I-0001



MC-RE3.81VXXC-R-0001




MC-RE3.81VXXC-RK-0001




3.81mm间距 Pitch: 3.81mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	M2	MC-RJ3.81HXXP-0001	2-24	MC-IP3.81-X		
额定电流 Rated current	[A]	8	扭矩 Torque	[N·m]	-	MC-RJ3.81HXXP-K-0001	2-24		
额定电压 Rated voltage	[V]	160	固定螺钉 Fixed screw	M2.5	MC-RJ3.81HXXP-I-0001	2-24			
硬导线截面积 Solid	[mm ²][AWG]	0.2-1.5	扭矩 Torque	[N·m]	0.3				
柔性导线截面积 Flexible	[mm ²][AWG]	0.2-1.5	剥线长度 Strip length	[mm]	8-9				
额定冲击电压 Rated impulse voltage	[KV]	2.5							

MC-RJ3.81HXXP-0001



MC-RJ3.81HXXP-K-0001



MC-RJ3.81HXXP-I-0001

