



5.08mm间距 Pitch: 5.08mm

产品信息Product Information				产品信息Product Information				订货号/通道数 Order /Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data				锁线螺钉 Locking crew				M2	MC-RA5.08HXXC-0001	2-24	
额定电流 Rated current	[A]	8	8	扭矩 Torque	[N·m]	0.2		MC-RA5.08HXXC-K-0001	2-24		
额定电压 Rated voltage	[V]	320	300	固定螺钉 Fixed screw		M2.5		MC-RA5.08HXXC-I-0001	2-24		
硬导线截面积 Solid	[mm²][AWG]	0.2-1.5	24-16	扭矩 Torque	[N·m]	0.3					
柔性导线截面积 Flexible	[mm²][AWG]	0.2-1.5	24-16	剥线长度 Strip length	[mm]	7-8					
额定冲击电压 Rated impulse voltage	[KV]	4	-								

MC-RA5.08HXXC-0001



MC-RA5.08HXXC-K-0001




MC-RA5.08HXXC-I-0001




5.08mm间距 Pitch: 5.08mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order /Poles No.		附件Accessory
IEC/UL数据 IEC/UL Data		IEC	UL	锁线螺钉 Locking crew	M3	MC-RB5.08HXXB-0001	2-24	MC-JP5.0-XX
额定电流 Rated current	[A]	12	15	扭矩 Torque	[N·m]	0.5	MC-RB5.08HXXB/100-0001	2-24
额定电压 Rated voltage	[V]	320	300	固定螺钉 Fixed screw	M2.5	MC-RB5.08HXXB-I-0001	2-24	MC-R-MSTB
硬导线截面积 Solid	[mm²][AWG]	0.2-2.5	24-12	扭矩 Torque	[N·m]	0.3	MC-RB5.08HXXB-K-0001	2-24
柔性导线截面积 Flexible	[mm²][AWG]	0.2-2.5	24-12	剥线长度 Strip length	[mm]	7-8	MC-RB5.08HXXB-K/100-0001	2-24
额定冲击电压 Rated impulse voltage	[KV]	4	-					


MC-RB5.08HXXB-0001




MC-RB5.08HXXB/100-0001




MC-RB5.08HXXB-I-0001




MC-RB5.08HXXB-I/100-0001



MC-RB5.08HXXB-K-0001




MC-RB5.08HXXB-K/100-0001




5.08mm间距 Pitch: 5.08mm

产品信息Product Information				产品信息Product Information				订货号/通道数 Order /Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL		锁线螺钉 Locking crew		M3	MC-RB5.08HXXC-0001	2-24	MC-WG5.0-X		
额定电流 Rated current	[A]	18	15	扭矩 Torque	[N·m]	0.5 <th>MC-RB5.08HXXC-K-0001</th> <th>2-24</th> <th>MC-GW5.08-XX</th> <td></td> <td></td>	MC-RB5.08HXXC-K-0001	2-24	MC-GW5.08-XX		
额定电压 Rated voltage	[V]	320	300	固定螺钉 Fixed screw		M2.5	MC-RB5.08HXXC-I-0001	2-24	MC-JP5.0-X		
硬导线截面积 Solid	[mm²][AWG]	0.2-2.5	24-12	扭矩 Torque	[N·m]	0.3			MC-R-MSTB		
柔性导线截面积 Flexible	[mm²][AWG]	0.2-2.5	24-12	剥线长度 Strip length	[mm]	7-8					
额定冲击电压 Rated impulse voltage	[KV]	4	-								


MC-RB5.08HXXC-0001



MC-RB5.08HXXC-K-0001




MC-RB5.08HXXC-I-0001




5.08mm间距 Pitch: 5.08mm

产品信息Product Information				产品信息Product Information				订货号/通道数 Order /Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data		IEC	UL	锁线螺钉 Locking crew		M2.5	MC-RBF5.08HXXC-0001	2-24	MC-JP5.0-X		
额定电流 Rated current		[A]	18	15	扭矩 Torque		[N·m]	0.5	MC-RBF5.08HXXC-K-0001	2-24	MC-R-MSTB
额定电压 Rated voltage		[V]	320	300	固定螺钉 Fixed screw		M2.5		MC-RBF5.08HXXC-I-0001	2-24	
硬导线截面积 Solid		[mm²][AWG]	0.2-2.5	24-12	扭矩 Torque		[N·m]	0.3			
柔性导线截面积 Flexible		[mm²][AWG]	0.2-2.5	24-12	剥线长度 Strip length		[mm]	11-12			
额定冲击电压 Rated impulse voltage		[KV]	4	-							

MC-RBF5.08HXXC-0001



MC-RBF5.08HXXC-K-0001



MC-RBF5.08HXXC-I-0001

