


5.08mm间距 Pitch: 5.08mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.			附件Accessory		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	M3		MC-RE5.08VXXC-0001	2-24		MC-JP5.0-X		
额定电流 Rated current	[A]	12	扭矩 Torque	[N·m]	0.5	MC-RE5.08VXXC-K-0001	2-24		MC-R-MSTB		
额定电压 Rated voltage	[V]	320	固定螺钉 Fixed screw	M2.5		MC-RE5.08VXXC-I-0001	2-24				
硬导线截面积 Solid [mm²][AWG]	0.2-2.5	24-12	扭矩 Torque	[N·m]	0.3	MC-RE5.08VXXC-R-0001	2-24				
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5	24-12	剥线长度 Strip length	[mm]	7-8	MC-RE5.08VXXC-RK-0001	2-24				
额定冲击电压 Rated impulse voltage	[KV]	4									

MC-RE5.08VXXC-0001


MC-RE5.08VXXC-K-0001

MC-RE5.08VXXC-I-0001



MC-RE5.08VXXC-R-0001

MC-RE5.08VXXC-RK-0001




5.08mm间距 Pitch: 5.08mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.			附件Accessory		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-		MC-RJ5.08HXXP-0001	2-24		MC-R-MSTB		
额定电流 Rated current	[A]	12	扭矩 Torque	[N·m]	-	MC-RJ5.08HXXP-D-0001	2-24				
额定电压 Rated voltage	[V]	320	固定螺钉 Fixed screw	M2.5		MC-RJ5.08HXXP-I-0001	2-24				
硬导线截面积 Solid [mm²][AWG]	0.2-2.5	24-12	扭矩 Torque	[N·m]	0.3	MC-RJ5.08HXXP-K-0001	2-24				
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5	24-12	剥线长度 Strip length	[mm]	10-11						
额定冲击电压 Rated impulse voltage	[KV]	4									


MC-RJ5.08HXXP-0001

MC-RJ5.08HXXP-D-0001



MC-RJ5.08HXXP-I-0001

MC-RJ5.08HXXP-K-0001



5.08mm间距 Pitch: 5.08mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.			附件Accessory		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-		MC-RN5.08VXXP-0001	2-24		MC-R-MSTB		
额定电流 Rated current	[A]	12	扭矩 Torque	[N·m]	-	MC-RN5.08VXXP-K-0001	2-24				
额定电压 Rated voltage	[V]	320	固定螺钉 Fixed screw	M2.5		MC-RN5.08VXXP-R-0001	2-24				
硬导线截面积 Solid [mm²][AWG]	0.2-2.5	24-12	扭矩 Torque	[N·m]	0.3	MC-RN5.08VXXP-RK-0001	2-24				
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5	24-12	剥线长度 Strip length	[mm]	10-11						
额定冲击电压 Rated impulse voltage	[KV]	4									


MC-RN5.08VXXP-0001

MC-RN5.08VXXP-K-0001



MC-RN5.08VXXP-R-0001

MC-RN5.08VXXP-RK-0001



5.08mm间距 Pitch: 5.08mm

产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.			附件Accessory		
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-		MC-RJT5.08HXXP-0001	2-24		MC-R-MSTB		
额定电流 Rated current	[A]	12	扭矩 Torque	[N·m]	-	MC-RJT5.08HXXP-K-0001	2-24				
额定电压 Rated voltage	[V]	320	固定螺钉 Fixed screw	M2.5							
硬导线截面积 Solid [mm²][AWG]	0.2-2.5	24-12	扭矩 Torque	[N·m]	0.3						
柔性导线截面积 Flexible [mm²][AWG]	0.2-2.5	24-12	剥线长度 Strip length	[mm]	10-11						
额定冲击电压 Rated impulse voltage	[KV]	4									

MC-RJT5.08HXXP-0001

MC-RJT5.08HXXP-K-0001

