

6.35mm间距 Pitch: 6.35mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 32 30	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 630 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm²]/AWG] 0.2-6.0 24-10	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm²]/AWG] 0.2-6.0 24-10	剥线长度 Strip length	[mm] 8-9
额定冲击电压 Rated impulse voltage	[KV] 6	-	-



MC-TG6.35HXXC-0001



订货号/通道数 Order /Poles No.	附件Accessory
MC-TG6.35HXXC-0001	2P-12P

7.62mm间距 Pitch: 7.62mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 24 15	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 630 250	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm²]/AWG] 0.2-2.5 24-12	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm²]/AWG] 0.2-2.5 24-12	剥线长度 Strip length	[mm] 7-8
额定冲击电压 Rated impulse voltage	[KV] 6	-	-



MC-TD7.62HXXC-0001



订货号/通道数 Order /Poles No.	附件Accessory
MC-TD7.62HXXC-0001	2P-16P

6.35mm间距 Pitch: 6.35mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 41 30	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 1000 600	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm²]/AWG] 0.2-6.0 24-10	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm²]/AWG] 0.2-6.0 24-10	剥线长度 Strip length	[mm] 8-9
额定冲击电压 Rated impulse voltage	[KV] 8	-	-



MC-TH/F6.35HXXC-0001



订货号/通道数 Order /Poles No.	附件Accessory
MC-TH/F6.35HXXC-0001	1P-12P

7.62mm间距 Pitch: 7.62mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 32 30	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 630 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm²]/AWG] 0.2-2.5 24-12	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm²]/AWG] 0.2-2.5 24-12	剥线长度 Strip length	[mm] 7-8
额定冲击电压 Rated impulse voltage	[KV] 6	-	-



MC-TF7.62HXXC-0001



订货号/通道数 Order /Poles No.	附件Accessory
MC-TF7.62HXXC-0001	2P-24P

7.5mm间距 Pitch: 7.5mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 32 30	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 630 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm²]/AWG] 0.2-4.0 24-10	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm²]/AWG] 0.2-4.0 24-10	剥线长度 Strip length	[mm] 8-9
额定冲击电压 Rated impulse voltage	[KV] 6	-	-



MC-TH7.5HXXC-0001



订货号/通道数 Order /Poles No.	附件Accessory
MC-TH7.5HXXC-0001	2P-12P

7.62mm间距 Pitch: 7.62mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 32 30	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 630 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm²]/AWG] 0.2-6.0 24-10	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm²]/AWG] 0.2-6.0 24-10	剥线长度 Strip length	[mm] 8-9
额定冲击电压 Rated impulse voltage	[KV] 6	-	-



MC-TG7.62HXXC-0001




订货号/通道数 Order /Poles No.	附件Accessory
MC-TG7.62HXXC-0001	2P-12P


7.5mm间距 Pitch: 7.5mm

产品信息Product Information	产品信息Product Information	订货号/通道数 Order /Poles No.	附件Accessory
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	-
额定电流 Rated current	[A] 41 36	扭矩 Torque	[N·m] -
额定电压 Rated voltage	[V] 1000 600	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm²]/AWG] 0.2-10 24-8	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm²]/AWG] 0.2-6 24-8	剥线长度 Strip length	[mm] 13-15
额定冲击电压 Rated impulse voltage	[KV] 8	-	-


MC-TC7.5HXXP-0001




MC-TC/F7.5HXXP-0001




MC-TC/B7.5HXXP-0001




MC-TC7.5VXXP-0001



MC-TC/F7.5VXXP-0001



MC-TC/B7.5VXXP-0001



9.52mm间距 Pitch: 9.52mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 32 30	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 1000 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm²]/AWG] 0.2-6.0 24-10	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm²]/AWG] 0.2-6.0 24-10	剥线长度 Strip length	[mm] 8-9
额定冲击电压 Rated impulse voltage	[KV] 6	-	-



MC-TG9.52HXXC-0001



订货号/通道数 Order /Poles No.	附件Accessory
MC-TG9.52HXXC-0001	2P-12P

9.52mm间距 Pitch: 9.52mm

产品信息Product Information		产品信息Product Information	
IEC/UL数据 IEC/UL Data	IEC UL	锁线螺钉 Locking crew	M3
额定电流 Rated current	[A] 32 30	扭矩 Torque	[N·m] 0.5
额定电压 Rated voltage	[V] 1000 300	固定螺钉 Fixed screw	-
硬导线截面积 Solid	[mm²]/AWG] 0.2-6.0 24-10	扭矩 Torque	[N·m] -
柔性导线截面积 Flexible	[mm²]/AWG] 0.2-6.0 24-10	剥线长度 Strip length	[mm] 8-9
额定冲击电压 Rated impulse voltage	[KV] 8	-	-



MC-TH9.52HXXC-0001



订货号/通道数 Order /Poles No.	附件Accessory
MC-TH9.52HXXC-0001	2P-12P