









多用弹簧连接器(MCS连接器) MCS connectors with spring-cage clamp






5.08mm间距孔型连接器 5.08mm Female connectors									
产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-	-	4581XX	2-24	45897X	
额定电流 Rated current	[A]	12 15	扭矩 Torque	[N·m]	-	4581XX/010	2-24	4585XX	
额定电压 Rated voltage	[V]	320 300	固定螺钉 Fixed screw	-	-	4506XX/030	2-24	450021	
硬导线截面积 Solid	[mm²][AWG]	0.2-2.5 28-12	扭矩 Torque	[N·m]	-	4506XX/050	2-24	450023	
柔性导线截面积 Flexible	[mm²][AWG]	0.2-2.5 28-12	剥线长度 Strip length	[mm]	8-9			450014	
额定冲击电压 Rated impulse voltage	[KV]	4.0	-	-	-				

4581XX	4581XX/010	4581XX/030
带固定脚with fixing flange	带弹钉with snap in mounting feet	带弹钉with snap in mounting feet
		
4581XX/050		
带卡接钩with locking device		
		

5.08mm间距针型连接器 5.08mm Male connector with spring-cage clamp									
产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-	-	4584XX	2-24	45897X	
额定电流 Rated current	[A]	12 15	扭矩 Torque	[N·m]	-	4584XX/010	2-24	4585XX	
额定电压 Rated voltage	[V]	320 300	固定螺钉 Fixed screw	-	-	4584XX/030	2-24	450021	
硬导线截面积 Solid	[mm²][AWG]	0.2-2.5 28-12	扭矩 Torque	[N·m]	-	4584XX/060	2-24	450023	
柔性导线截面积 Flexible	[mm²][AWG]	0.2-2.5 28-12	剥线长度 Strip length	[mm]	8-9			450014	
额定冲击电压 Rated impulse voltage	[KV]	4.0	-	-	-				

4584XX	4584XX/010	4584XX/030
带固定脚with fixing flange	带弹钉with snap in mounting feet	带弹钉with snap in mounting feet
		
4584XX/060		
带穿墙固定器with mounting ears		
		

5.08mm间距焊针插座 5.08mm Solder pin									
产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-	-	4582XX	2-24	450015	
额定电流 Rated current	[A]	12 15	扭矩 Torque	[N·m]	-	4582XX-01D	2-24		
额定电压 Rated voltage	[V]	320 300	固定螺钉 Fixed screw	-	-	4583XX	2-24		
硬导线截面积 Solid	[mm²][AWG]	-	扭矩 Torque	[N·m]	-	4583XX-00D	2-24		
柔性导线截面积 Flexible	[mm²][AWG]	-	剥线长度 Strip length	[mm]	-				
额定冲击电压 Rated impulse voltage	[KV]	4.0	-	-	-				

4582XX	4582XX-01D	
		
4583XX	4583XX-00D	4583XX-04D
		

5.08mm间距孔型带焊针 5.08mm Female connector with spring-cage clamp with solder pin									
产品信息Product Information			产品信息Product Information			订货号/通道数 Order / Poles No.		附件Accessory	
IEC/UL数据 IEC/UL Data	IEC	UL	锁线螺钉 Locking crew	-	-	45825X	2-24		
额定电流 Rated current	[A]	12 15	扭矩 Torque	[N·m]	-	45835X	2-24		
额定电压 Rated voltage	[V]	320 300	固定螺钉 Fixed screw	-	-				
硬导线截面积 Solid	[mm²][AWG]	-	扭矩 Torque	[N·m]	-				
柔性导线截面积 Flexible	[mm²][AWG]	-	剥线长度 Strip length	[mm]	-				
额定冲击电压 Rated impulse voltage	[KV]	4.0	-	-	-				

45825X	45835X
直针型vertical solder pin	弯针型right angle solder pin
