


斜面双层八线接线端子
Doule level angled type terminal block 8-wire







斜面双层八线等电位接线端子
Doule level angled type terminal block with equipotential bonder 8-wire

		技术参数Technical Parameter			技术参数Technical Parameter		
尺寸Size		厚度Thickness	宽度Width	高度Height	厚度Thickness	宽度Width	高度Height
注：安装NS35/7.5导轨后的高度 Note：Height With DIN Rail NS 35/7.5	[mm]	5.2	115.2	53	5.2	115.2	53
额定参数Rated Parameters		IEC	UL		IEC	UL	
额定电压Rated Voltage	[V]	800	*		800	*	
额定电流Rated Current	[A]	20	*		20	*	
接线容量Wire Range		刚性Solid	柔性Fine Stranded	带冷压头Furrule	刚性Solid	柔性Fine Stranded	带冷压头Furrule
	[mm^2]	0.2-4.0	0.2-2.5	0.2-2.5	0.2-4.0	0.2-2.5	0.2-2.5
	[AWG]	26-12	26-12	26-12	26-12	26-12	26-12
其余参数Other Parameters							
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94			V0			V0	
剥线长度Strip length	[mm]		8-10			8-10	

		订货信息Order Information	订货信息Order Information
产品Product	颜色Colour	订货号Order NO.	订货号Order NO.
适配NS 35/7.5导轨 **Can Be Used For DIN Rail NS 35/7.5**	灰Gray	TPDS2.5-4-GY	TPDS2.5-4-PV(黑色)
	橙Orange	TPDS2.5-4-OG	
	蓝Blue	TPDS2.5-4-BU	
		配套附件Accessory	配套附件Accessory
端板Cover Plate		订货号Order NO.	订货号Order NO.
厚度2.2mm Thickness2.2mm	灰Gray	TPDS2.5-4-GY-EC	TPDS2.5-4-GY-EC
	橙Orange	TPDS2.5-4-OG-EC	TPDS2.5-4-OG-EC
	蓝Blue	*	*
补偿端板Compensatory Plate		订货号Order NO.	订货号Order NO.
厚度1.00mm Thickness1.00mm	灰Gray	*	*
跨接件Jumper			
位数Poles No.	颜色Colour	订货号Order NO.	订货号Order NO.
2	黄Yellow	TJA5.2-2	TJA5.2-2
3	黄Yellow	TJA5.2-3	TJA5.2-3
4	黄Yellow	TJA5.2-4	TJA5.2-4
...	.....	.....	.....
9	黄Yellow	TJA5.2-9	TJA5.2-9
10	黄Yellow	TJA5.2-10	TJA5.2-10
闪电标记Front Marker		订货号Order NO.	订货号Order NO.
5PCS一条		*	*
正面标记Lightning Marker		订货号Order NO.	订货号Order NO.
10PCS一条		*	*
正面标记和侧面标记Front And Side Marker		订货号Order NO.	订货号Order NO.
可提供印字服务Printing Service		TMB5.2-120	TMB5.2-120





斜面双层八线接地端子
Doule level angled type ground terminal block 8-wire

		技术参数Technical Parameter		
尺寸Size		厚度Thickness	宽度Width	高度Height
注：安装NS35/7.5导轨后的高度 Note：Height With DIN Rail NS 35/7.5	[mm]	5.2	115.2	53
额定参数Rated Parameters		IEC	UL	
额定电压Rated Voltage	[V]			
额定电流Rated Current	[A]			
接线容量Wire Range		刚性Solid	柔性Fine Stranded	带冷压头Furrule
	[mm^2]	0.2-4.0	0.2-2.5	0.2-2.5
	[AWG]	26-12	26-12	26-12
其余参数Other Parameters				
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94			V0	
剥线长度Strip length	[mm]		8-10	

		订货信息Order Information
产品Product	颜色Colour	订货号Order NO.
适配NS 35/7.5导轨 **Can Be Used For DIN Rail NS 35/7.5**	灰Gray	TPDS2.5-4-PE
	橙Orange	
	蓝Blue	
		配套附件Accessory
端板Cover Plate		订货号Order NO.
厚度2.2mm Thickness2.2mm	灰Gray	TPDS2.5-4-GY-EC
	橙Orange	TPDS2.5-4-OG-EC
	蓝Blue	*
补偿端板Compensatory Plate		订货号Order NO.
厚度1.00mm Thickness1.00mm	灰Gray	*
跨接件Jumper		
位数Poles No.	颜色Colour	订货号Order NO.
2	黄Yellow	TJA5.2-2
3	黄Yellow	TJA5.2-3
4	黄Yellow	TJA5.2-4
...	.....	.....
9	黄Yellow	TJA5.2-9
10	黄Yellow	TJA5.2-10
闪电标记Front Marker		订货号Order NO.
5PCS一条		*
正面标记Lightning Marker		订货号Order NO.
10PCS一条		*
正面标记和侧面标记Front And Side Marker		订货号Order NO.
可提供印字服务Printing Service		TMB5.2-120