







	1.5mm² 三线启动器端子 Initiator terminal block 3-wire			1.5mm² 三线执行器端子 Actuator terminal block 3-wire		
	技术参数Technical Parameter			技术参数Technical Parameter		
尺寸Size	厚度Thickness	宽度Width	高度Height	厚度Thickness	宽度Width	高度Height
注：安装NS35/7.5导轨后的高度 Note：Height With DIN Rail NS 35/7.5 [mm]	3.5	74.5	41.5	3.5	74.5	41.5
额定参数Rated Parameters	IEC	UL		IEC	UL	
额定电压Rated Voltage [V]	250	*		250	*	
额定电流Rated Current [A]	13.5	*		13.5	*	
接线容量Wire Range	刚性Solid	柔性Fine Stranded	带冷压头Furrule	刚性Solid	柔性Fine Stranded	带冷压头Furrule
[mm²]	0.14-1.5	0.14-1.5	0.14-1.5	0.14-1.5	0.14-1.5	0.14-1.5
[AWG]	26-14	26-14	26-14	26-14	26-14	26-14
其余参数Other Parameters						
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94		V0			V0	
剥线长度Strip length [mm]		8-9			8-9	
产品Product 颜色Colour	订货信息Order Information 订货号Order NO.			订货信息Order Information 订货号Order NO.		
适配NS 35/7.5导轨 Can Be Used For DIN Rail NS 35/7.5 — 灰Gray	TPIO1.5-S-3			TPIO1.5-S-3-PE		
灰，带红灯With red light	TPIO1.5-S-3-LR24			*		
灰，带绿灯With green light	TPIO1.5-S-3-LG24			*		
橙Orange	*					
	配套附件Accessory			配套附件Accessory		
端板Cover Plate	订货号Order NO.			订货号Order NO.		
厚度2.2mm Thickness2.2mm 灰Gray	TPIO1.5-S-3-GY-EA			TPIO1.5-S-3-GY-EA		
橙Orange	TPIO1.5-S-3-OG-EA			TPIO1.5-S-3-OG-EA		
蓝Blue	TPIO1.5-S-3-BU-EA			TPIO1.5-S-3-BU-EA		
补偿端板Compensatory Plate	订货号Order NO.			订货号Order NO.		
厚度1.00mm Thickness1.00mm 灰Gray	*			*		
跨接件Jumper						
位数Poles No. 颜色Colour	订货号Order NO.			订货号Order NO.		
2 黄Yellow	TJA3.5-2			TJA3.5-2		
3 黄Yellow	TJA3.5-3			TJA3.5-3		
4 黄Yellow	TJA3.5-4			TJA3.5-4		
... .	.....			.....		
9 黄Yellow	TJA3.5-9			TJA3.5-9		
10 黄Yellow	TJA3.5-10			TJA3.5-10		
正面标记Front Marker	订货号Order NO.			订货号Order NO.		
10位PCS	*			*		
正面标记和侧面标记Front And Side Marker	订货号Order NO.			订货号Order NO.		
可提供印字服务Printing Service	TMB3.5-100			TMB3.5-100		

	1.5mm² 四线启动器端子 Initiator terminal block 4-wire			1.5mm² 四线执行器端子 Actuator terminal block 4-wire		
	技术参数Technical Parameter			技术参数Technical Parameter		
	厚度Thickness	宽度Width	高度Height	厚度Thickness	宽度Width	高度Height
	3.5	90.8	41.5	3.5	90.8	41.5
	IEC	UL		IEC	UL	
	250	*		250	*	
	13.5	*		13.5	*	
	刚性Solid	柔性Fine Stranded	带冷压头Furrule	刚性Solid	柔性Fine Stranded	带冷压头Furrule
	0.14-1.5	0.14-1.5	0.14-1.5	0.14-1.5	0.14-1.5	0.14-1.5
	26-14	26-14	26-14	26-14	26-14	26-14
		V0			V0	
		8-9			8-9	
	订货信息Order Information			订货信息Order Information		
	订货号Order NO.			订货号Order NO.		
	TPIO1.5-S-4			TPIO1.5-S-4-PE		
	TPIO1.5-S-4-LR24			*		
	TPIO1.5-S-4-LG24			*		
	*			*		
	配套附件Accessory			配套附件Accessory		
	订货号Order NO.			订货号Order NO.		
	TPIO1.5-S-4-GY-EA			TPIO1.5-S-4-GY-EA		
	TPIO1.5-S-4-OG-EA			TPIO1.5-S-4-OG-EA		
	TPIO1.5-S-4-BU-EA			TPIO1.5-S-4-BU-EA		
	订货号Order NO.			订货号Order NO.		
	*			*		
	订货号Order NO.			订货号Order NO.		
	TJA3.5-2			TJA3.5-2		
	TJA3.5-3			TJA3.5-3		
	TJA3.5-4			TJA3.5-4		
	.....			.....		
	TJA3.5-9			TJA3.5-9		
	TJA3.5-10			TJA3.5-10		
	订货号Order NO.			订货号Order NO.		
	*			*		
	订货号Order NO.			订货号Order NO.		
	TMB3.5-100			TMB3.5-100		

表示产品开发中，了解更多产品详情请来电咨询。

The product is under development. Please contact us for more information.