





		4mm²,双层接线端子 Double level terminl block			4mm²,双层等电位接线端子 Double level terminl block with equipotential bonder		
		技术参数Technical Parameter			技术参数Technical Parameter		
尺寸Size		厚度Thickness	宽度Width	高度Height	厚度Thickness	宽度Width	高度Height
注：安装NS35/7.5导轨后的高度 Note: Height With DIN Rail NS 35/7.5		6.2	69.9	64.5	6.2	69.9	64.5
额定参数Rated Parameters		IEC	UL		IEC	UL	
额定电压Rated Voltage		800	600		800	600	
额定电流Rated Current		32	30		32	30	
接线容量Wire Range		刚性Solid	柔性Fine Stranded	带冷压头Furrule	刚性Solid	柔性Fine Stranded	带冷压头Furrule
		0.2-6	0.2-4	0.2-4	0.2-6	0.2-4	0.2-4
		26-10	26-10	26-10	26-10	26-10	26-10
螺钉类型Screw Type		M3			M3		
扭矩Torque		0.5			0.5		
其余参数Other Parameters							
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94		V0			V0		
剥线长度Strip length		9-11			9-11		
		订货信息Order Information			订货信息Order Information		
产品Product		颜色Colour			订货号Order NO.		
适配NS 35/7.5导轨 Can Be Used For DIN Rail NS 35/7.5	灰Gray	TUD4-2-GY			TUD4-2-PV (黑色)		
	橙Orange	TUD4-2-OG					
	蓝Blue	TUD4-2-BL					
		配套附件Accessory			配套附件Accessory		
盖板Cover Plate		颜色Colour			订货号Order NO.		
盖板Cover Plate	灰Gray	TUD2.5-2-GY-EA			TUD2.5-2-GY-EA		
	橙Orange	TUD2.5-2-OG-EA			TUD2.5-2-OG-EA		
跨接件Jumper							
极数Poles No.		订货号Order NO.			订货号Order NO.		
2		TJA6.2-2			TJA6.2-2		
3		TJA6.2-3			TJA6.2-3		
4		TJA6.2-4			TJA6.2-4		
5		TJA6.2-5			TJA6.2-5		
6		TJA6.2-6			TJA6.2-6		
7		TJA6.2-7			TJA6.2-7		
8		TJA6.2-8			TJA6.2-8		
9		TJA6.2-9			TJA6.2-9		
10		TJA6.2-10			TJA6.2-10		
正面标记(小)Front Marker(Small)		订货号Order NO.			订货号Order NO.		
可提供印字服务Printing Service		TMB6.2-100			TMB6.2-100		
正面标记(大)Front Marker(Big)		订货号Order NO.			订货号Order NO.		
可提供印字服务Printing Service		306801			306801		



		2.5mm²,双层接地端子 Double level ground terminl block			4mm²,双层接地端子 Double level ground terminl block		
		技术参数Technical Parameter			技术参数Technical Parameter		
尺寸Size		厚度Thickness	宽度Width	高度Height	厚度Thickness	宽度Width	高度Height
注：安装NS35/7.5导轨后的高度 Note: Height With DIN Rail NS 35/7.5		5.2	69.9	64.5	6.2	69.9	64.5
额定参数Rated Parameters		IEC	UL		IEC	UL	
额定电压Rated Voltage		*	*		*	*	
额定电流Rated Current		*	*		*	*	
接线容量Wire Range		带冷压头Furrule	柔性Fine Stranded	刚性Solid	带冷压头Furrule	柔性Fine Stranded	刚性Solid
		0.2-4	0.2-2.5	0.25-2.5	0.2-6	0.2-4	0.25-4
		26-12	26-12	26-12	26-12	26-10	26-10
螺钉类型Screw Type		M2.5			M3		
扭矩Torque		0.4			0.5		
其余参数Other Parameters							
绝缘材料/阻燃等级，符合UL94 Insulating Material / Flame Retardant Grade, Conforming To UL94		V0			V0		
剥线长度Strip length		9-11			9-11		
		订货信息Order Information			订货信息Order Information		
产品Product		颜色Colour			订货号Order NO.		
适配NS 35/7.5导轨 Can Be Used For DIN Rail NS 35/7.5		黄绿Yellow green			TUD4-2-PE		